



TECHNICAL DATASHEET

X-PRO D60 / REF.30900

SPRAYING MACHINE



Easy-to use diesel versatile spraying machine for outdoor spraying.

Made in France, it is equipped with a button control panel for simplified use, an automatic accelerator and a water dosing meter.

APPLICATIONS

Large wall jobs in hydraulic coatings, mortars, E.W.I.

...

Motor	Kohler LDW 1003
Motor power	18 kW - stage V
Fuel	Diesel B7
Diesel tank	25 L
Cooling	liquid
Rotation speed	2500 tr/min
Number of cylinders	3
Consumption	3,1 L/h
Hydraulic system	28 L
Compressor	twin-cylinder
Compressor flow-rate at 4 bar	400 L/min
Engine monitoring panel	complete
Hydraulic controls	manual
Mixer rotation speed setting	yes
Pump speed setting	yes
Automatic accelerator control	yes
Mixer tank capacity	230 L
Mixer drainage plug	3 inches
Water sprinkler pipe	yes
Water meter	yes
Mixing paddle	yes
Rotation	2 directions
Loading height	86 cm
Hopper capacity	200 L
Hopper drainage plug	3 inches
Variable flow-rate	from 0 to 60 L/min (3,6 m3/h)
Pressure	from 0 to 40 bar
Max. grain size	up to 6 mm
Pump	MAP 11
Pump reverse operation	yes
HP washer max pressure	140 bar
HP washer flow-rate	11 L/min
Overall length with tow bar	3,55 m
Overall length without tow bar	3,09 m
Overall width	1,26 m
Height at the highest point	1,29 m
Weight when full with oil and diesel	720 kg
Noise level	101 Lwa
Delivery height	50 m
Max. hose length	60 m

DELIVERED WITH

- a MAP 11 pump
- a Ø35 x 13,30 m product hose M50 x F35
- a Ø35 x 13,30 m product hose M35 x F35
- a Ø25 x 5 m hose M35 x M25
- a Ø10 x 33 m air hose
- a spraying lance
- eight nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22)
- three grouting nozzles (Ø10, 12 & 14)
- two Ø30 cleaning balls
- two Ø50 cleaning balls
- a greasing pump with a grease cartridge
- a pressure controller adapter
- a pressure controller
- a complete high pressure washer lance
- a 10 m high pressure washer hose
- a storage carry-case
- a suspension strap



EUROMAIR